

Forza 200 Daylight

1. Accurate daylight-balanced color at 5600K, CRI: 98 TLCI: 97
2. 220W, 37540 Lux @ 1m (with reflector).
3. 11 Built-in Practical Lighting Effects:
INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire,
Bad Bulb, Firework, Explosion and Welding.
4. Separate design for fixture head and control unit & Dual power supply.
5. Standard Bowens Mount.
6. USB port to support firmware updates.



On-board



DMX



2.4G



APP



NANLINK BOX

Forza 300/500 Daylight

1. Accurate daylight-balanced color at 5600K, CRI: 98 and TLCI:95
2. Rated Power: 340W/545W.
3. 4 Built-in Practical Lighting Effects: Storm, Flash, TV, Bad Bulb
4. Separate design for fixture head and control unit & Dual power supply.
5. Standard Bowens Mount.
6. The control methods include on-board, 2.4G, NANLINK APP, DMX.



On-board



DMX



2.4G



APP



NANLINK BOX

Includes

Light x 1, Control Unit x 1, Power Adapter x 1, Power Cable 3M x 1, Connecting Cable 2.5M x 1, COB Protective Cap x 1, Reflector x 1, Light Stand Clamp x 1, Carrying Bag x 1, User Manual x 1



Forza *Technical Data*

Model	<i>Forza 500</i>	<i>Forza 720</i>	<i>Forza 720B</i>
Rated Power	545W	800W	800W
Input Voltage/Current	DC48V/12.5A Max, AC100-240V 50/60Hz	DC48V/16.67A Max, AC100-240V 50/60Hz	DC48V/16.67A Max, AC100-240V 50/60Hz
CRI	98	95	Average 96
TLCI	95	96	Average 97
CCT	5600K	5600K	2700K-6500K
Dimming	0 to 100 % continuous	0 to 100 % continuous	0 to 100 % continuous
Control	On-board, 2.4G, DMX	On-board, 2.4G, Bluetooth, DMX/RDM	On-board, 2.4G, Bluetooth, DMX/RDM
Product Size	330 × 225 × 140mm / 12.99 × 8.86 × 5.51"	475 × 231 × 142mm / 18.7 × 9.09 × 5.59"	518 × 228 × 142mm / 20.39 × 8.98 × 5.59"
Product Weight	Light fixture	2.7 kg / 5.95 lb	4.8kg / 10.58lb
	Light Fixture +Control Unit	4.7kg / 10.36lb	9kg / 19.84lb

Illumination(lux / fc)

Model/CCT	<i>Forza 500(5600K)</i>			<i>Forza 720(5600K)</i>			<i>Forza 720B(5600K)</i>		
Distance	1M	3M	5M	3M	5M	7M	3M	5M	7M
Light Only	20070 lux 1865 fc	2276 lux 211 fc	888 lux 82 fc	3777 lux 351 fc	1629 lux 151 fc	903 lux 84 fc	3116 lux 289 fc	1407 lux 131 fc	716 lux 67 fc
With Reflector	93350 lux 8672 fc	8245 lux 766 fc	2933 lux 272 fc	10200 lux 948 fc	3945 lux 366 fc	2211 lux 205 fc	7919 lux 736 fc	3152 lux 293 fc	1714 lux 159 fc
With Fresnel lens Spot 10°	N/A	25656 lux 2383 fc	9001 lux 836 fc	24980 lux 2321 fc	8618 lux 801 fc	4340 lux 403 fc	17650 lux 1640 fc	6344 lux 589 fc	3234 lux 300 fc
With Fresnel lens Flood 45°	49960 lux 4641 fc	5822 lux 541 fc	2187 lux 203 fc	7832 lux 720 fc	3128 lux 291 fc	1787 lux 166 fc	7363 lux 684 fc	2884 lux 268 fc	1607 lux 149 fc