

Forza FM Mount LED Spot Light

Palm-sized, Lightweight Design, New Ecosystem

Forza 60 **Daylight**

1. Accurate daylight-balanced color at 5600K, CRI: 98 and TLCI: 95
2. Palm-sized body with mighty output: 18820 Lux @ 1m (5600K) with reflector.
3. 4 Built-in Practical Lighting Effects: Storm, Flash, TV, Bad Bulb.
4. FM Mount.
5. Power anywhere, run with AC adapter, NP-F batteries or a V-mount battery.



On-board



2.4G



APP



NANLINK BOX

Forza 60B **Bi-color**

1. Variable color temperature of 2700K-6500K, CRI: Average 96, TLCI: Average 98.
2. Palm-sized body with mighty output: 13830 Lux @ 1m (5600K) with reflector.
3. 12 Built-in Practical Effects: CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Papparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding.
4. FM Mount.
5. Power anywhere, run with AC adapter, NP-F batteries or a V-mount battery.
6. Support firmware updates via USB port & Wireless control via 2.4G, Bluetooth, NANLINK APP.



On-board



Bluetooth



2.4G



APP



NANLINK BOX



Forza 60



Forza 60B

Includes

Light x 1, Power Adapter x 1, Power Cable 3M x 1, Reflector x 1, Carrying Bag x 1, BH-FZ60 Battery Grip x 1, AS-BA-FMM Bowens Adapter x 1, COB Protective Cap x 1, User Manual x 1

Model	Forza 60B
Rated Power	80W
Input voltage/current	DC15V/6A Max, AC100-240V 50/60Hz
CRI	Average 96
TLCI	Average 98
CCT	2700K-6500K
Dimming	0 - 100 % continuous
Control	On-board, 2.4G, Wifi, Bluetooth
Dimensions	Light size (without COB protective cap) : 199 × 85 × 105mm / 7.83 × 3.35 × 4.13" Power adapter size: 163 × 66 × 32mm / 6.42 × 2.60 × 1.26"
Weight	Light fixture: 0.83kg / 1.83lb Power adapter: 0.45kg / 0.99lb Power Cable 3M: 0.12kg / 0.26lb Reflector: 0.14kg / 0.31lb
Certifications	CE, UKCA, PSE, FCC, ROHS, KUCAS, NCC

Illumination(lux/fc)

Type	Distance	1M	2M	3M
Without Lens	2700K	1701Lux / 158fc	419Lux / 39fc	196Lux / 18fc
	3200K	1919Lux / 178fc	480Lux / 45fc	224Lux / 21fc
	5600K	2246Lux / 209fc	564Lux / 52fc	263Lux / 24fc
	6500K	2205Lux / 205fc	555Lux / 52fc	260Lux / 24fc
With Standard reflector	2700K	9820Lux / 912fc	2081Lux / 193fc	877Lux / 81fc
	3200K	11480Lux / 1066fc	2420Lux / 225fc	1030Lux / 96fc
	5600K	13830Lux / 1285fc	2927Lux / 272fc	1251Lux / 116fc
	6500K	13590Lux / 1263fc	2913Lux / 271fc	1244Lux / 116fc
With Fresnel Lens spot 10°	2700K	23240Lux / 2159fc	5600Lux / 520fc	2443Lux / 227fc
	3200K	27400Lux / 2545fc	6418Lux / 596fc	2813Lux / 261fc
	5600K	33450Lux / 3108fc	7944Lux / 738fc	3476Lux / 323fc
	6500K	33530Lux / 3115fc	7890Lux / 733fc	3466Lux / 322fc

With Fresnel Lens flood 45°	2700K	5242Lux / 487fc	1277Lux / 119fc	567Lux / 53fc
	3200K	5978Lux / 555fc	1458Lux / 135fc	646Lux / 60fc
	5600K	7100Lux / 660fc	1736Lux / 161fc	777Lux / 72fc
	6500K	7065Lux / 656fc	1735Lux / 161fc	772Lux / 72fc